

KABSON FIRE FIGHTER



**THINK SAFETY
THINK US**

☎ 18008914226

✉ INFO@KABSONFIRE.COM

🌐 WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



KABSON FIRE FIGHTER

KABSON

COMPANY PROFILE

GREETINGS FROM **KAY BEE SALES & SERVICES** "KABSON" FIRE FIGHTER IS THE MOST ADORABLE FIRE SUPPRESSION & PROTECTION BRAND PROMOTED BY KAY BEE SALES & SERVICES.

WE ARE AN **ISO CERTIFIED** ISO 9001:2015 PIONEER IN **FIRE & SAFETY EQUIPMENTS**. WE ARE SPECIALIZED IN PORTABLE/TROLLEY MOUNTED/WHEELED FIRE EXTINGUISHER, AUTOMATIC FIRE SUPPRESSION SYSTEM, WIRED & WIRELESS FIRE DETECTION SYSTEM, FIREFIGHTING EQUIPMENT, INDUSTRIAL SAFETY, PPE EQUIPMENTS, GAS DETECTION SYSTEM, FIRE HYDRANT, SPRINKLER SYSTEM, HYDRANT VALVES, SWINGING HOSE REELS, SIGNAGE'S, FIRE BLANKET , ESCAPE GEARS ETC.

ALONG WITH THESE WE ARE **MASTER IN CONSULTANCY & HANDLING TURNKEY PROJECT'S IN FIRE DETECTION, SUPPRESSION & EVACUATION.**

SINCE OUR INCEPTION TILL DATE WE HAVE SEVERAL MNC'S, MAJOR CORPORATE, GOVERNMENT ESTABLISHMENTS & PSU, UNIVERSITIES, SCHOOLS, HOSPITALS & IT FIRMS IN OUR PORTFOLIO.

CURRENTLY WE ARE AN **NSIC LISTED** ORGANIZATION SERVING PAN INDIA DEDICATED SALES & SERVICE NETWORK WITH AGGRESSIVE MANPOWER, CHANEL PARTNER'S & STRATEGIC ALLIANCES.

KINDLY VISIT OUR SITE **KABSONFIRE.COM** OR **KBFIRESAFETY.COM** FOR OUR NEAREST SERVICE STATION OR MAIL US AT **INFO@KABSONFIRE.COM** OR **ADMIN@KBFIRESAFETY.COM** OR CALL OUR HELPLINE NO:- **18008914226**


LIST OF CERTIFIED PRODUCTS

1. ISI MARK ABC TYPE STORED PRESSURE DRY CHEMICAL POWDER.
2. ISI MARK HFC236FA STORED PRESSURE CLEAN AGENT.
3. ISI MARK AFF FOAM STORED PRESSURE CONCENTRATES.
4. ISI MARK CARBON DIOXIDE STORED PRESSURE CYLINDERS
5. ISI MARK WATER STORED PRESSURE CYLINDERS

UPCOMING OTHER PRODUTS

- **D CLASS POWDER (SUITABLE FOR METAL FIRE)**
- **POTASSIUM BI CARBONATE BASED DRY CHEMICAL POWDER**
- **OFFEX**
- **FLAME RETARDANT CHEMICALS**
- **FLUOROPROTEIN FOAM**
- **ALCOHOL RESISTANT FOAM**
- **HIGH EXPANSION FOAM**
- **CONCRETE FOAM**
- **ISI MARK CO2 GAS CARTRIDGES**
- **ISI MARK FIRST AID HOSE REEL DRUM**
- **ISI MARK CO2 TYPE FIRE EXTINGUISHERS**
- **ISI MARK LANDING VALVES**
- **ISI MARK MALE FEMALE INSTANTANEOUS COUPLINGS**
- **ISI MARK SHORT BRANCH PIPE**
- **ISI MARK NOZZLES**
- **FIRE FIGHTING EQUIPMENTS**
- **WIRED & WIRELESS FIRE DETECTION SYSTEM**
- **AUTOMATIC FIRE SUPPRESSION**
- **HOME & OFFICE SECURITY SYSTEM**
- **ESCAPE GEARS CONTAINING - SET OF FIRE BLANKET & BREATHABLE FIRE MASK**

KINDLY NOTE SOME OF THE ABOVE PRODUCTS ARE ALREADY TRADED BY US

 18008914226

 INFO@KABSONFIRE.COM

 WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



ABC TYPE DRY CHEMICAL POWDER FOR A,B,C & E CLASS OF FIRE

IS : 15683



CM/L : 9922293



TECHNICAL CLASSIFICATION / CHARACTERISTICS

INDIAN STANDARD	15683
CAPACITY	1 KG 2KG 4KG 6KG 9KG
TYPE	STORED PRESSURE
EXTINGUISHING MEDIA	DRY POWDER ABC POWDER CONFIRMING TO ISO 4308
EXPELLANT	NITROGEN
OPERATING TEMPERATURE	-10 TO +56° C
MINIMUM EFFECTIVE DISCHARGE (%)	MORE THAN 90 %
HYDRAULIC TEST PRESSURE	27 KG / CM 2
DISCHARGE TIME (SECS) MINIMUM	8 8 8 13 13
RESISTANCE TO IMPACT	YES
THROW MORE THEN	2 METERS
TAPPING TESTS (500 STROKES)	CONFORMS
RESISTANCE TO CORROSION (SALT SPRAY TEST)	YES
FIRE RATING	1A,21B 1A,21B 2A, 55B 3A,89B 4A,144B

APPLICATION AREAS: PAPERS, WOOD, TEXTILES, RUBBER, PLASTICS, OIL, PAINT, PETROCHEMICAL PRODUCTS, RESINS, COMPRESSED GASES LIKE ACETYLENE, LPG, CNG, ELECTRICAL AND SOPHISTICATED ELECTRONIC EQUIPMENTS



18008914226

INFO@KABSONFIRE.COM

WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



MULTIPURPOSE CLEAN AGENT FOR A, B, C & E CLASS OF FIRE

IS : 15683



CM/L : 9922293



↑ KEEP THIS SIDE UP

HFC236FA

FIRE EXTINGUISHER

↑ KEEP THIS SIDE UP

IS : 15683

CM/L 9922293

INSTRUCTIONS: Inspect Monthly. Check That Extinguisher is Charged, Undamaged and Seal is in fact, make sure Discharge Tube and / or Nozzle is Unobstructed
MAINTENANCE: Examine three months to ensure that Safety And Tamper Seal are not Broken or Missing. Ensure by Weighing Or Lifting That Extinguisher is Full and Also to Ensure that it is Not Damaged, Corroded, Leaking or has a Clogged Nozzle. Check That pressure Gauge Reading or Indicators is in the Operable Range that is Green Zone.
PRECAUTIONS: Contents of the Extinguishers are under Pressure. So Do not Puncture, Incinerate or Temper with the Body of the Extinguishers Store Away from Direct Sunlight. Do not rely on Partially Used Extinguisher.
USE: Always Break open The Seal only in the event of Fire. Always Direct the discharge at the Base of Fire and not Over the fire
RECHARGE: RETURN TO THE AUTHORIZED RECHARGER FOR RECHARGING

RECORDS: RECORD MAINTENANCE AND RECHARGE DATES

A USE OF WOOD, PAPER, TEXTILES & RUBBISH

B USE OF FLAMMABLE LIQUIDS

C USE OF FLAMMABLE GASES

E USE OF ELECTRICAL EQUIPMENT

Remember the **PASS** Word

Pull Pull the pin or other actions to unlock the extinguisher

Aim Aim at the base (bottom)

Squeeze Squeeze the lever

Sweep Sweep the spray from left to right

CAPACITY

FIRE RATING

MODEL NO.

MFG. YEAR

GROSS WEIGHT

NET WEIGHT

MRP

SR. NO.

OPERATING TEMPERATURE : -10° TO +55° C

RECHARGE IMMEDIATELY AFTER USE

18008914226

info@kabsonfire.com

www.kabsonfire.com

Marketed by **KAY BEE SALES & SERVICES ODISHA, INDIA**

Manufactured by **FAL CON FIREMATICS PVT. LTD. GURGAON, HR INDIA**

TECHNICAL CLASSIFICATION / CHARACTERISTICS

INDIAN STANDARD	15683
CAPACITY	2 KG
TYPE	STORED PRESSURE
EXTINGUISHING MEDIA	HFC 227 EA BASED CLEAN AGENT
EXPELLANT	NITROGEN
OPERATING TEMPERATURE	-10 TO 55° C
MINIMUM EFFECTIVE DISCHARGE (%)	MORE THAN 95 %
HYDRAULIC TEST PRESSURE	35 KG / CM 2
THROW MINIMUM	1 METER
DISCHARGE TIME (SEC)	8
RESISTANCE TO IMPACT	YES
RESISTANCE TO VIBRATION	YES
TAPPING TESTS (500 STROKES)	CONFORMS
RESISTANCE TO CORROSION (SALT SPRAY TEST)	YES
FIRE RATING	8B



APPLICATION AREAS: HOSPITAL AND NURSING HOMES, OPERATION THEATRES, LABORATORIES, ALL OFFICE INVOLVING USE OF COSTLY ELECTRONIC EQUIPMENT, MULTIPLEX THEATRE, BPO, DEPARTMENTAL STORE, FURNITURE SHOWROOMS, FACTORY E.T.C

18008914226

INFO@KABSONFIRE.COM

WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



CARBON DIOXIDE FIRE EXTINGUISHER FOR B, C & E CLASS OF FIRE

IS : 15683



CML : 9922293



CARBON DIOXIDE FIRE EXTINGUISHER

KABSON FIRE FIGHTER

Remember the **PASS** Word

Pull Pull the pin (or other motion) to unlock the extinguisher.

Aim Aim at the base (bottom).

Squeeze Squeeze the lever.

Sweep Sweep the spray from left to right.

USE FOR FLAMMABLE LIQUID

USE FOR ELECTRICAL EQUIPMENT

USE FOR FLAMMABLE GASES

OPERATING TEMPERATURE: -10 TO +55° C

RECHARGE IMMEDIATELY AFTER USE

CAPACITY: FIRE RATING: MODEL NO. MFG. YEAR

SR. NO. GROSS WEIGHT NET WEIGHT MRP

Marketed by KAY BEE SALES & SERVICES ODISHA, INDIA

Manufactured by FALCON FIREMATICS PVT. LTD. GURGAON, HR INDIA

FIRE

CARBON DIOXIDE FIRE EXTINGUISHER

KABSON FIRE FIGHTER

Remember the **PASS** Word

Pull Pull the pin (or other motion) to unlock the extinguisher.

Aim Aim at the base (bottom).

Squeeze Squeeze the lever.

Sweep Sweep the spray from left to right.

USE FOR FLAMMABLE LIQUID

USE FOR ELECTRICAL EQUIPMENT

USE FOR FLAMMABLE GASES

OPERATING TEMPERATURE: -10 TO +55° C

RECHARGE IMMEDIATELY AFTER USE

CAPACITY: FIRE RATING: MODEL NO. MFG. YEAR

SR. NO. GROSS WEIGHT NET WEIGHT MRP

Marketed by KAY BEE SALES & SERVICES ODISHA, INDIA

Manufactured by FALCON FIREMATICS PVT. LTD. GURGAON, HR INDIA

FIRE

TECHNICAL CLASSIFICATION / CHARACTERISTICS

INDIAN STANDARD	15683
ISI MARK	YES
CAPACITY	2KG 4.5 KG
TYPE	STORED PRESSURE
EXTINGUISHING MEDIA	CARBON DIOXIDE GAS CONFIRMING TO IS 15222
EXPELLANT	SELF EXPELLING
FILLING RATIO, MAX	0.667
OPERATING TEMPERATURE	-10 TO +55° C
MINIMUM EFFECTIVE DISCHARGE (%)	MORE THAN 95 %
THROW MINIMUM	1 METERS 1 METERS
DISCHARGE TIME (SECS) MINIMUM	8 8
RESISTANCE TO VARIATION	YES
FIRE RATING	8B 13 B

APPLICATION AREAS: FIRES INVOLVING OF ALL FLAMABLE LIQUIDS , GASES, MACHINERY FIRES, ELECTRICAL AND SOPHISTICATED ELECTRONIC EQUIPMENT FIRES, TRANSFORMER AND SWITCH GEAR FIRES E.T.C



USE FOR FLAMMABLE LIQUID



USE FOR ELECTRICAL EQUIPMENT



USE FOR FLAMMABLE GASES

18008914226

INFO@KABSONFIRE.COM

WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



WATER FIRE EXTINGUISHER FOR A CLASS OF FIRE



IS : 15683



CM/L : 9922293



WATER
FIRE EXTINGUISHER



IS : 15683



CM/L : 9922293

KABSON

KABSON
FIRE FIGHTER



USE OF
WOOD,
PAPER,
TEXTILES &
RUBBISH

CAPACITY	<input type="text"/>
FIRE RATING	<input type="text"/>
MODEL NO.	<input type="text"/>
MFG. YEAR	<input type="text"/>
GROSS WEIGHT	<input type="text"/>
NET WEIGHT	<input type="text"/>
MRP	<input type="text"/>
SR. NO.	<input type="text"/>

INSTRUCTIONS: Inspect Monthly. Check That Extinguisher Is Charged, Undamaged and Seal is in fact, make sure Discharge Tube and/or Nozzle is Unobstructed
MAINTENANCE: Examine three months to ensure that Safety And Tamper Seal are not Broken or Missing. Ensure by Weighing Or Lifting That Extinguisher is Full and Also to Ensure that it is Not Damaged, Corroded, Leaking or has a Clogged Nozzle. Check That pressure Gauge Reading or Indicators is in the Operable Range that is Green Zone
PRECAUTIONS: Contents of the Extinguishers are under Pressure. So Do not Puncture, Incinerate or temper with the Body of the Extinguishers Store Away from Direct Sunlight. Do not rely on Partially Used Extinguisher. Always Break open The Seal only in the event of Fire. Always Direct the discharge at the Base of Fire and not Over the fire
USE: AFTER ANY USE RECHARGE IMMEDIATELY
RECHARGE: RETURN TO THE AUTHORIZED RECHARGER FOR RECHARGING
RECORDS: RECORD MAINTENANCE AND RECHARGE DATES

OPERATING TEMPERATURE : -10° TO +55° C

RECHARGE IMMEDIATELY AFTER USE

18008914226

info@kabsonfire.com

www.kabsonfire.com

Marketed by KAY BEE SALES & SERVICES

ODISHA, INDIA

Manufactured by FALCON FIREMATICS PVT. LTD.

GURGAON, HR INDIA



TECHNICAL CLASSIFICATION / CHARACTERISTICS

INDIAN STANDARD	15683
CAPACITY	9 LITRES
TYPE	STORED PRESSURE
EXTINGUISHING MEDIA	WATER
EXPELLANT	NITROGEN
OPERATING TEMPERATURE	+5 TO 55° C
MINMUM EFFECTIVE DISCHARGE (%)	MORE THAN 95 %
HYDRAULIC TEST PRESSURE	27 KG / CM 2
THROW MINIMUM	2 METERS
DISCHARGE TIME (SEC)	13
RESISTANCE TO IMPACT	YES
RESIATANCE TO VIBRATION	YES
TAPPING TESTS (500 STROKES)	CONFORMS
RESISTANCE TO CORROSION (SALT SPRAY TEST)	YES
FIRE RATING	3A

**APPLICATION AREAS: ALL A CLASS
FIRE WHICH INCLUDES MATERIALS
LIKE WOOD , PAPER, CLOTH,
FIBRES, PLASTICS, RUBBERS E.T.C**

18008914226

INFO@KABSONFIRE.COM

WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



MECHANICAL FOAM TYPE FOR A & B CLASS OF FIRE



IS : 15683



C/M/L : 9922293



FOAM
FIRE EXTINGUISHER



IS : 15683



C/M/L : 9922293

KABSON

KABSON
FIRE FIGHTER

INSTRUCTIONS: Inspect Monthly. Check That Extinguisher Is Charged, Undamaged and Seal is in fact, make sure Discharge Tube and / or Nozzle is Unobstructed
MAINTENANCE: Examining three months to ensure that Safety And Tamper Seal are not Broken or Missing. Ensure by Weighing Or Lifting That Extinguisher is Full and Also to Ensure that it is Not Damaged, Corroded, Leaking or has a Clogged Nozzle. Check That pressure Gauge Reading or indicators is in the Operable Range that is Green Zone.
PRECAUTIONS: Contents of the Extinguishers are under Pressure. So Do not Puncture, Incline or temper with the Body of the Extinguishers Store Away from Direct Sunlight. Do not rely on Partially Used Extinguisher.
 Always Break open The Seal only in the event of Fire. Always Direct the discharge at the Base of Fire and not Over the fire
USE: AFTER ANY USE RECHARGE IMMEDIATELY
RECHARGE: RETURN TO THE AUTHORIZED RECHARGER FOR RECHARGING
RECORDS: RECORD MAINTENANCE AND RECHARGE DATES

Remember the **PASS** Word

- P** Pull
Pull the pin (or other motion) to unlock the extinguisher.
- A** Aim
Aim at the base (bottom).
- S** Squeeze
Squeeze the lever.
- S** Sweep
Sweep the spray from left to right.

A



USE OF WOOD, PAPER, TEXTILES & RUBBISH

B



USE OF FLAMMABLE LIQUIDS

OPERATING TEMPERATURE : -10° TO +55° C

RECHARGE IMMEDIATELY AFTER USE

18008914226

info@kabsonfire.com

www.kabsonfire.com

Marketed by **KAY BEE SALES & SERVICES** ODISHA, INDIA

Manufactured by **FALCON FIREMATICS PVT. LTD.** GURGAON, HR INDIA

CAPACITY	<input type="text"/>	FIRE RATING	<input type="text"/>
MODEL NO.	<input type="text"/>	MFG. YEAR	<input type="text"/>
GROSS WEIGHT	<input type="text"/>	NET WEIGHT	<input type="text"/>
MRP	<input type="text"/>	SR. NO.	<input type="text"/>

TECHNICAL CLASSIFICATION / CHARACTERISTICS

INDIAN STANDARD	15683
CAPACITY	9 LITRES
TYPE	STORED PRESSURE
EXTINGUISHING MEDIA	AQUEOUS FILM FORMING CONFORMING TO IS 499
EXPELLANT	NITROGEN
OPERATING TEMPERATURE	+5 TO 55° C
MINIMUM EFFECTIVE DISCHARGE (%)	95 %
HYDRAULIC TEST PRESSURE	27 KG / CM 2
THROW MINIMUM	2 METERS
DISCHARGE TIME (SEC)	13
RESISTANCE TO IMPACT	YES
RESISTANCE TO VIBRATION	YES
TAPPING TESTS (500 STROKES)	CONFORMS
RESISTANCE TO CORROSION (SALT SPRAY TEST)	YES
FIRE RATING	3A, 34B



APPLICATION AREAS: ALL A & B CLASS FIRE INCLUDING WOOD, PAPER, TEXTILES, STATIONERY, VOLATABLE LIQUIDS LIKE OIL, PETROL, DIESEL, KEROSENE, SOLVENTS & CHEMICALS, WAX, RESINS AND OTHER PETRO CHEMICAL PRODUCTS E.T.C

18008914226

INFO@KABSONFIRE.COM

WWW.KABSONFIRE.COM

KAY BEE SALES & SERVICES ODISHA, INDIA



FIRE FIGHTING EQUIPMENTS

IS : 15683



CML : 9922293



FIRE SIGNAGES

FLUORESCENT STRIPS



FIRE EXTINGUISHER STAND

BUCKET STAND

KABSON FIRE POINT OUR IMPROVISATION



KABSON **FIRE FIGHTER**

Master of Fire Suppression

K A B S O N

*Most Adorable Brand in
Fire & Safety Equipments*


LIKE, SHARE AND FOLLOW US ON



YouTube



Marketed By : Kay Bee Sales Services Odisha, India

 18008914226

 INFO@KABSONFIRE.COM
SALES@KBFIRESAFETY.COM

 WWW.KABSONFIRE.COM
WWW.KBFIRESAFETY.COM